

CRANE

125# Bronze Valves

Fig. 1700 & 1700-S RS Gate


125# psi Steam, Water, Oil & Gas
200 psi Cold Working Pressure Rising Stem
Screwed Bonnet - Full Ports
PTFE Packing
S = Solder Ends



Size	Catalog #
1/4"	CV-1700-0.25
3/8"	CV-1700-0.375
1/2"	CV-1700-0.50
3/4"	CV-1700-0.75
1"	CV-1700-1.00
1 1/4"	CV-1700-1.25
1 1/2"	CV-1700-1.50
2"	CV-1700-2.00
2 1/2"	CV-1700-2.50
3"	CV-1700-3.00

Fig. 1701 & 1701-S NRS Gate


125# psi Steam, Water, Oil & Gas
200 psi Cold Working Pressure
Non-Rising Stem - One Piece Bonnet
Full Ports - PTFE Packing
S = Solder Ends



Size	Catalog #
1/4"	CV-1701-0.25
3/8"	CV-1701-0.375
1/2"	CV-1701-0.50
3/4"	CV-1701-0.75
1"	CV-1701-1.00
1 1/4"	CV-1701-1.25
1 1/2"	CV-1701-1.50
2"	CV-1701-2.00
2 1/2"	CV-1701-2.50
3"	CV-1701-3.00

Fig. 1702 & 1702-S RS Globe


125# psi Steam, Water, Oil & Gas
200 psi Cold Working Pressure
Rising Stem - Screwed Bonnet
Internal Bronze Disc & Seat
S = Solder Ends




Size	Catalog #
1/4"	CV-1702-0.25
3/8"	CV-1702-0.375
1/2"	CV-1702-0.50
3/4"	CV-1702-0.75
1"	CV-1702-1.00
1 1/4"	CV-1702-1.25
1 1/2"	CV-1702-1.50
2"	CV-1702-2.00



Size	Catalog #
3/8"	CV-1700-S-0.375
1/2"	CV-1700-S-0.50
3/4"	CV-1700-S-0.75
1"	CV-1700-S-1.00
1 1/4"	CV-1700-S-1.25
1 1/2"	CV-1700-S-1.50
2"	CV-1700-S-2.00
2 1/2"	CV-1700-S-2.50
3"	CV-1700-S-3.00



Size	Catalog #
3/8"	CV-1701-S-0.375
1/2"	CV-1701-S-0.50
3/4"	CV-1701-S-0.75
1"	CV-1701-S-1.00
1 1/4"	CV-1701-S-1.25
1 1/2"	CV-1701-S-1.50
2"	CV-1701-S-2.00
2 1/2"	CV-1701-S-2.50
3"	CV-1701-S-3.00




Size	Catalog #
3/8"	CV-1702-S-0.375
1/2"	CV-1702-S-0.50
3/4"	CV-1702-S-0.75
1"	CV-1702-S-1.00
1 1/4"	CV-1702-S-1.25
1 1/2"	CV-1702-S-1.50
2"	CV-1702-S-2.00

Fig. 1707 Check Valve

125# psi Steam Basic Rating
200 psi Cold Working Pressure
T-Pattern Swing Check

- Installation Note: Always install with pressure under the disc in vertical or horizontal position.
 - Free-to-rotate bronze disc closes in a different position on the integral seat each time it operates.
- Threaded Ends




Size	Catalog #
1/4"	CV-1707-0.25
3/8"	CV-1707-0.375
1/2"	CV-1707-0.50
3/4"	CV-1707-0.75
1"	CV-1707-1.00
1 1/4"	CV-1707-1.25
1 1/2"	CV-1707-1.50
2"	CV-1707-2.00
2 1/2"	CV-1707-2.50
3"	CV-1707-3.00

Fig. 37 Y-Pattern Swing Check

125# psi Steam Basic Rating
200 psi Cold Working Pressure
Y-Pattern Swing Check

- Installation Note: Always install with pressure under the disc in vertical or horizontal position.
 - Seat can be reground in-line.
- Screwed Cap
Threaded Ends




Size	Catalog #
1/4"	CV-37-0.25
3/8"	CV-37-0.375
1/2"	CV-37-0.50
3/4"	CV-37-0.75
1"	CV-37-1.00
1 1/4"	CV-37-1.25
1 1/2"	CV-37-1.50
2"	CV-37-2.00
2 1/2"	CV-37-2.50
3"	CV-37-3.00

Fig. 29 Vertical Lift Check

125# psi Steam Basic Rating
200 psi Cold Working Pressure
One piece body - Bronze Disc

- Designed for upward flow only.
 - Vertical installation only.
 - Seats are integral with body.
- Excellent choke for suction lines and general service.



Size	Catalog #
1/4"	CV-29-0.25
3/8"	CV-29-0.375
1/2"	CV-29-0.50
3/4"	CV-29-0.75
1"	CV-29-1.00
1 1/4"	CV-29-1.25
1 1/2"	CV-29-1.50
2"	CV-29-2.00
2 1/2"	CV-29-2.50
3"	CV-29-3.00