

CRANE

150# Bronze Valves





Fig. 137 Y Check

150 psi Steam, Basic Rating
300 psi Cold Working Pressure
Y-Pattern Body Swing Check
Installation Note: Always install with pressure under the disc in vertical or horizontal position.

Threaded Ends - Screwed Cap

Size	Catalog #
1/4"	CV-137-0.25
3/8"	CV-137-0.375
1/2"	CV-137-0.50
3/4"	CV-137-0.75
1"	CV-137-1.00
1 1/4"	CV-137-1.25
1 1/2"	CV-137-1.50
2"	CV-137-2.00
2 1/2"	CV-137-2.50
3"	CV-137-3.00

Fig. 1342S Y Check




150 psi Steam, Basic Rating
300 psi Cold Working Pressure
Y-Pattern Body Swing Check
Installation Note: Always install with pressure under the disc in vertical or horizontal position.

Solder Ends - Screwed Cap

Size	Catalog #
1/2"	CV-1342-S-0.50
3/4"	CV-1342-S-0.75
1"	CV-1342-S-1.00
1 1/4"	CV-1342-S-1.25
1 1/2"	CV-1342-S-1.50
2"	CV-1342-S-2.00
2 1/2"	CV-1342-S-2.50
3"	CV-1342-S-3.00

Fig. 27TF Horizontal Lift Check




150 psi Steam, Basic Rating
300 psi Cold Working Pressure
Lift Check Design
PTFE Disc
Horizontal installation only.
Threaded Ends - Union Cap

Size	Catalog #
1/4"	CV-27TF-0.25
3/8"	CV-27TF-0.375
1/2"	CV-27TF-0.50
3/4"	CV-27TF-0.75
1"	CV-27TF-1.00
1 1/4"	CV-27TF-1.25
1 1/2"	CV-27TF-1.50
2"	CV-27TF-2.00

200# Bronze Valves

Fig. 422 RS Gate


200 psi Steam, Basic Rating
400 psi Cold Working Pressure
Rising Stem - Union Bonnet
Full Ports - Solid Wedge Disc - Bronze Seat
Threaded Ends



Size	Catalog #
1/4"	CV-422-0.25
3/8"	CV-422-0.375
1/2"	CV-422-0.50
3/4"	CV-422-0.75
1"	CV-422-1.00
1 1/4"	CV-422-1.25
1 1/2"	CV-422-1.50
2"	CV-422-2.00
2 1/2"	CV-422-2.50
3"	CV-422-3.00

Fig. 424 RS Gate


200 psi Steam, Basic Rating
400 psi Cold Working Pressure
Rising Stem - Bolted Union Bonnet
Full Ports - Solid Wedge Disc - 410 SS Seat Rings
Threaded Ends



Size	Catalog #
1/4"	CV-424-0.25
3/8"	CV-424-0.375
1/2"	CV-424-0.50
3/4"	CV-424-0.75
1"	CV-424-1.00
1 1/4"	CV-424-1.25
1 1/2"	CV-424-1.50
2"	CV-424-2.00
2 1/2"	CV-424-2.50
3"	CV-424-3.00

Fig. 426 NRS Gate


200 psi Steam, Basic Rating
400 psi Cold Working Pressure
Non-Rising Stem - Union Bonnet
Solid Wedge Disc - Full Ports - 410 SS Seat Rings
Threaded Ends



Size	Catalog #
1/4"	CV-426-0.25
3/8"	CV-426-0.375
1/2"	CV-426-0.50
3/4"	CV-426-0.75
1"	CV-426-1.00
1 1/4"	CV-426-1.25
1 1/2"	CV-426-1.50
2"	CV-426-2.00
2 1/2"	CV-426-2.50
3"	CV-426-3.00

Fig. 88 RS Globe / Needle Style


200 psi Steam, Basic Rating
400 psi Cold Working Pressure
Rising Stem - Screwed Bonnet
Integral Seat - Graphite Packing
Threaded Ends



Size	Catalog #
1/8"	CV-88-0.125
1/4"	CV-88-0.25
3/8"	CV-88-0.375
1/2"	CV-88-0.50
3/4"	CV-88-0.75


Fig. 89 RS Angle / Needle Style

200 psi Steam, Basic Rating
400 psi Cold Working Pressure
Rising Stem - Screwed Bonnet
Graphite Packing
Threaded Ends



Size	Catalog #
1/8"	CV-89-0.125
1/4"	CV-89-0.25
3/8"	CV-89-0.375
1/2"	CV-89-0.50
3/4"	CV-89-0.75

Fig. 36 Y Swing Check



150 psi Steam, Basic Rating
300 psi Cold Working Pressure
Y-Pattern Body Swing Check
Installation Note: Always install with pressure under the disc in vertical or horizontal position.
Threaded Ends - Screwed Cap

Size	Catalog #
1/4"	CV-137-0.25
3/8"	CV-137-0.375
1/2"	CV-137-0.50
3/4"	CV-137-0.75
1"	CV-137-1.00
1 1/4"	CV-137-1.25
1 1/2"	CV-137-1.50
2"	CV-137-2.00
2 1/2"	CV-137-2.50
3"	CV-137-3.00