


Fig. 622E RS Gate


300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure
 Rising Stem - Union Bonnet
 Full Ports - Solid Wedge Disc
 Threaded Ends



Size	Catalog #
1/4"	CV-622E-0.25
3/8"	CV-622E-0.375
1/2"	CV-622E-0.50
3/4"	CV-622E-0.75
1"	CV-622E-1.00
1 1/4"	CV-622E-1.25
1 1/2"	CV-622E-1.50
2"	CV-622E-2.00

Fig. 634E RS Gate


300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure to 2"
 600 psi Cold Working Pressure to 2 1/2" & 3"
 Rising Stem - Union Bolted Bonnet - Full Ports
 Solid Wedge Disc - SS Seat Ring - Threaded Ends



Size	Catalog #
1/4"	CV-634E-0.25
3/8"	CV-634E-0.375
1/2"	CV-634E-0.50
3/4"	CV-634E-0.75
1"	CV-634E-1.00
1 1/4"	CV-634E-1.25
1 1/2"	CV-634E-1.50
2"	CV-634E-2.00
2 1/2"	CV-634E-2.50
3"	CV-634E-3.00

Fig. 636E NRS Gate


300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure
 Non-Rising Stem - Union Bonnet
 Solid Wedge Disc - Full Ports - SS Seat Rings
 Threaded Ends



Size	Catalog #
1/4"	CV-636E-0.25
3/8"	CV-636E-0.375
1/2"	CV-636E-0.50
3/4"	CV-636E-0.75
1"	CV-636E-1.00
1 1/4"	CV-636E-1.25
1 1/2"	CV-636E-1.50
2"	CV-636E-2.00

Fig. 382P RS Globe


300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure to 2"
 600 psi Cold Working Pressure to 2 1/2" & 3"
 Rising Stem - Union Bonnet - Plug Type Disc
 450 Brinell Hardened SS Seat Ring - Threaded Ends



Size	Catalog #
1/4"	CV-382P-0.25
3/8"	CV-382P-0.375
1/2"	CV-382P-0.50
3/4"	CV-382P-0.75
1"	CV-382P-1.00
1 1/4"	CV-382P-1.25
1 1/2"	CV-382P-1.50
2"	CV-382P-2.00
2 1/2"	CV-382P-2.50
3"	CV-382P-3.00


Fig. 384P RS Angle

300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure to 2"
 Rising Stem - Union Bonnet - Plug Type Disc
 Wide Seating Surfaces
 450 Brinell Hardened SS Seat Ring - Threaded Ends



Size	Catalog #
1/4"	CV-384P-0.25
3/8"	CV-384P-0.375
1/2"	CV-384P-0.50
3/4"	CV-384P-0.75
1"	CV-384P-1.00
1 1/4"	CV-384P-1.25
1 1/2"	CV-384P-1.50
2"	CV-384P-2.00

Fig. 76E Y Swing Check




300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure to 2"
 600 psi Cold Working Pressure to 2 1/2" & 3"
 Y-Pattern Body Swing Check - Re grindable Seat
 Installation Note: Always install with pressure under the disc in vertical or horizontal position.
 Threaded Ends - Screwed Cap

Size	Catalog #
1/4"	CV-76E-0.25
3/8"	CV-76E-0.375
1/2"	CV-76E-0.50
3/4"	CV-76E-0.75
1"	CV-76E-1.00
1 1/4"	CV-76E-1.25
1 1/2"	CV-76E-1.50
2"	CV-76E-2.00
2 1/2"	CV-76E-2.50
3"	CV-76E-3.00

Fig. 366E Lift Check

300 psi Steam, Basic Rating
 1000 psi Cold Working Pressure
 Lift Check Design
 Union Cap
 Threaded Ends



Size	Catalog #
1/2"	CV-366E-0.50
3/4"	CV-366E-0.75
1"	CV-366E-1.00
1 1/4"	CV-366E-1.25
1 1/2"	CV-366E-1.50
2"	CV-366E-2.00