


**250# Boiler Blow-Off Valves**



**Fig. 4000-A**  
ASA Class - 250lb  
Max Blow-Off Pressure  
ASME Code 200PSI  
Iron Body  
Quick Open Screwed

Size	Catalog #
1"	EV-4000-A-08
1 1/4"	EV-4000-A-10
1 1/2"	EV-4000-A-12
2"	EV-4000-A-16
2 1/2"	EV-4000-A-20

Dimensions:




DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
F	3 5/8	3 5/8	4 1/2	4 5/8	5 1/4
J	4	4 3/4	5 1/4	5 1/4	6 1/4
L	9	9	15 1/4	15 1/4	23
O	55	55	55	60	60
S	1 5/8	1 3/4	2 1/8	2 3/16	2 3/4



**Fig. 4060-A**  
ASA Class - 250lb  
Max Blow-Off Pressure  
ASME Code 200PSI  
Iron Body  
Slow Open Screwed

Size	Catalog #
1"	EV-4060-A-08
1 1/4"	EV-4060-A-10
1 1/2"	EV-4060-A-12
2"	EV-4060-A-16
2 1/2"	EV-4060-A-20

Dimensions:




DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
F	3 5/8	3 5/8	4 1/2	4 5/8	5 1/4
H	8	8	10	10 1/2	10 1/2
J	13	13	14	14	15 1/2
N	9	9 1/2	12	12 1/2	13 1/2
S	5	5	5 1/2	5 1/2	5 1/2
W	9	9	9	9	12



**Fig. 4001-A**  
ASA Class - 250lb  
Max Blow-Off Pressure  
ASME Code 200PSI  
Iron Body  
Quick Open Flanged

Size	Catalog #
1"	EV-4001-A-08
1 1/4"	EV-4001-A-10
1 1/2"	EV-4001-A-12
2"	EV-4001-A-16
2 1/2"	EV-4001-A-20

Dimensions:




DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
B	7 1/2	7 1/2	8 3/8	9	10 3/8
J	4	4 3/4	5 1/4	5 1/4	6 1/4
L	9	9	15 1/4	15 1/4	23
O	55	55	55	60	60
S	1 5/8	1 3/4	2 1/8	2 3/16	2 3/4

**Fig. 4061-A**  
ASA Class - 250lb  
Max Blow-Off Pressure  
ASME Code 200PSI  
Iron Body  
Slow Open Flanged

Size	Catalog #
1 1/2"	EV-4061-A-12
2"	EV-4061-A-16
2 1/2"	EV-4061-A-20

Dimensions:



DIM	1 1/2"	2"	2 1/2"
B	8 3/8	9	10 3/8
H	10	10 1/2	10 1/2
J	14	14	15 1/2
N	12	12 1/2	13 1/2
S	5 1/2	5 1/2	5 1/2
W	9	9	12

