


300# Boiler Blow-Off Valves



Fig. 4000-S57
 ASA Class - 300lb
 Max Blow-Off Pressure
 ASME Code 490PSI
 Steel Body
 Quick Open Screwed

Size	Catalog #
1"	EV-4000-S57-08
1 ¹ / ₄ "	EV-4000-S57-10
1 ¹ / ₂ "	EV-4000-S57-12
2"	EV-4000-S57-16
2 ¹ / ₂ "	EV-4000-S57-20

Dimensions:




DIM	1"	1 ¹ / ₄ "	1 ¹ / ₂ "	2"	2 ¹ / ₂ "
F	5	5 ¹ / ₄	6	6 ¹ / ₄	13 ³ / ₈
J	4	4 ³ / ₄	5 ¹ / ₄	5 ¹ / ₄	6 ¹ / ₄
L	9	9	15 ¹ / ₄	15 ¹ / ₄	23
O	55	55	55	60	60
S	1 ⁵ / ₈	1 ³ / ₄	2 ¹ / ₈	2 ¹ / ₁₆	2 ³ / ₄



Fig. 4060-S57
 ASA Class - 300lb
 Max Blow-Off Pressure
 ASME Code 490PSI
 Steel Body
 Slow Open Screwed

Size	Catalog #
1"	EV-4060-S57-08
1 ¹ / ₄ "	EV-4060-S57-10
1 ¹ / ₂ "	EV-4060-S57-12
2"	EV-4060-S57-16
2 ¹ / ₂ "	EV-4060-S57-20

Dimensions:




DIM	1"	1 ¹ / ₄ "	1 ¹ / ₂ "	2"	2 ¹ / ₂ "
F	5	5 ¹ / ₄	6	6 ¹ / ₄	13 ³ / ₈
H	7 ¹ / ₄	7 ¹ / ₄	7 ¹ / ₄	7 ¹ / ₄	9 ¹ / ₂
J	11 ¹ / ₂	12	12	12 ¹ / ₂	16
N	11	10	10 ¹ / ₂	13	13
S	4 ³ / ₄	4 ³ / ₄	5 ¹ / ₄	5 ¹ / ₄	6
W	9	9	9	9	12



Fig. 4001-S57
 ASA Class - 300lb
 Max Blow-Off Pressure
 ASME Code 490PSI
 Steel Body
 Quick Open Flanged

Size	Catalog #
1"	EV-4001-S57-08
1 ¹ / ₄ "	EV-4001-S57-10
1 ¹ / ₂ "	EV-4001-S57-12
2"	EV-4001-S57-16
2 ¹ / ₂ "	EV-4001-S57-20

Dimensions:




DIM	1"	1 ¹ / ₄ "	1 ¹ / ₂ "	2"	2 ¹ / ₂ "
B	7 ⁵ / ₈	7 ⁵ / ₈	8 ³ / ₄	9	12
J	4	4 ³ / ₄	5 ¹ / ₄	5 ¹ / ₄	6 ¹ / ₄
L	9	9	15 ¹ / ₄	15 ¹ / ₄	23
O	55	55	55	60	60
S	1 ⁵ / ₈	1 ³ / ₄	2 ¹ / ₈	2 ¹ / ₁₆	2 ³ / ₄



Fig. 4061-S57
 ASA Class - 300lb
 Max Blow-Off Pressure
 ASME Code 490PSI
 Steel Body
 Slow Open Flanged

Size	Catalog #
1"	EV-4061-S57-08
1 ¹ / ₄ "	EV-4061-S57-10
1 ¹ / ₂ "	EV-4061-S57-12
2"	EV-4061-S57-16
2 ¹ / ₂ "	EV-4061-S57-20

Dimensions:



DIM	1"	1 ¹ / ₄ "	1 ¹ / ₂ "	2"	2 ¹ / ₂ "
B	7 ⁵ / ₈	7 ⁵ / ₈	8 ⁷ / ₈	9	12
H	7 ¹ / ₄	7 ¹ / ₄	7 ¹ / ₄	7 ¹ / ₄	9 ¹ / ₂
J	11 ¹ / ₂	12	12	12 ¹ / ₂	16
N	11	10	10 ¹ / ₂	13	13
S	4 ³ / ₄	4 ³ / ₄	5 ¹ / ₈	5 ¹ / ₈	6 ¹ / ₂
W	9	9	9	9	12