


600# Boiler Blow-Off Valves



Fig. 4000-S58
ASA Class - 600lb
Max Blow-Off Pressure
ASME Code 935PSI
Steel Body
Quick Open Screwed

Size	Catalog #
1"	EV-4000-S58-08
1 1/4"	EV-4000-S58-10
1 1/2"	EV-4000-S58-12
2"	EV-4000-S58-16
2 1/2"	EV-4000-S58-20

Dimensions:




DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
F	5	5 1/4	6	6 1/4	13 3/8
J	4	4 3/4	5 1/4	5 1/4	6 1/4
L	9	9	15 1/4	15 1/4	23
O	55	55	55	60	60
S	1 5/8	1 3/4	2 1/8	2 1/16	2 3/4



Fig. 4060-S58
ASA Class - 600lb
Max Blow-Off Pressure
ASME Code 935PSI
Steel Body
Slow Open Screwed

Size	Catalog #
1"	EV-4060-S58-08
1 1/4"	EV-4060-S58-10
1 1/2"	EV-4060-S58-12
2"	EV-4060-S58-16
2 1/2"	EV-4060-S58-20

Dimensions:




DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
F	5	5 1/4	6	6 1/4	13 3/8
H	7 1/4	7 1/4	7 1/4	7 1/4	9 1/2
J	11 1/2	12	12	12 1/2	16
N	11	10	10 1/2	13	13
S	4 3/4	4 3/4	5 1/8	5 1/8	6 1/2
W	9	9	9	9	12



Fig. 4001-S58
ASA Class - 600lb
Max Blow-Off Pressure
ASME Code 935PSI
Steel Body
Quick Open Flanged

Size	Catalog #
1"	EV-4001-S58-08
1 1/4"	EV-4001-S58-10
1 1/2"	EV-4001-S58-12
2"	EV-4001-S58-16
2 1/2"	EV-4001-S58-20

Dimensions:




DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
B	8 1/2	9	10 1/2	11 7/8	15
J	4	4 3/4	5 1/4	5 1/4	6 1/4
L	9	9	15 1/4	15 1/4	23
O	55	55	55	60	60
S	1 5/8	1 3/4	2 1/8	2 1/16	2 3/4



Fig. 4061-S58
ASA Class - 600lb
Max Blow-Off Pressure
ASME Code 935PSI
Steel Body
Slow Open Flanged

Size	Catalog #
1"	EV-4061-S58-08
1 1/4"	EV-4061-S58-10
1 1/2"	EV-4061-S58-12
2"	EV-4061-S58-16
2 1/2"	EV-4061-S58-20

Dimensions:



DIM	1"	1 1/4"	1 1/2"	2"	2 1/2"
B	8 1/2	9	10 1/2	11 7/8	15
H	7 1/4	7 1/4	7 1/4	7 1/4	9 1/2
J	11 1/2	12	12	12 1/2	16
N	11	10	10 1/2	13	13
S	4 3/4	4 3/4	5 1/8	5 1/8	6 1/2
W	9	9	9	9	12