

Cast Iron Flanged Fittings

125 lb. Standard, Black, Faced and Drilled.



A. 90° Elbows B. 45° Elbows C. Reducing Elbows D. 90° Long Radius Elbows E. Tees F. Reducing Tees G. Crosses H. Laterals I. Concentric Reducers J. Eccentric Reducers

Size	A.	B.	C.	D.	E.	F.	G.	H.	I.	J.
1 1/2"										
2"										
2 1/2"										
3"										
4"										
5"										
6"										
8"										

SUR-TEF Joint Sealant Replaces Gor-Tex



Easy To Install

A gasket that comes on a spool, that's Sur-Tef Joint Sealant. Select the size you need, from 1/8" to 3/4" in diameter, cut off the length required with a pair of scissors and your gasket is ready to be applied. The adhesive stripe holds the Joint Sealant in place. Cross the ends at a bolt hole and tighten up. Temperature range -450° to +500°. Pressures to 2000lbs.

Size	Price
1/8" x 100'	
3/16" x 75'	
1/4" x 50'	
3/8" x 25'	
1/2" x 15'	
5/8" x 15'	
3/4" x 15'	

Red Rubber Gaskets

Full Face 1/8" thick
150 lb.



Size	Price
1/2"	
3/4"	
1"	
1 1/4"	
1 1/2"	
2"	
2 1/2"	
3"	
4"	
5"	
6"	
8"	
10"	
12"	

All Purpose Flange Gaskets



Companion Flange Gaskets 1/16" Thick



Ring Type

Size	150lb	300lb
1/2"		
3/4"		
1"		
1 1/4"		
1 1/2"		
2"		
2 1/2"		
3"		
3 1/2"		
4"		
5"		
6"		
8"		
10"		
12"		
14"		
16"		
18"		

Full Face

Size	150lb	300lb
1/2"		
3/4"		
1"		
1 1/4"		
1 1/2"		
2"		
2 1/2"		
3"		
3 1/2"		
4"		
5"		
6"		
8"		
10"		
12"		
14"		
16"		
18"		

Flexitallic

For Use on ANSI B 6.5 Raised and Flat Face Flanges



Style CG Gaskets

Size	150lb	300lb	600lb
1/2"			
3/4"			
1"			
1 1/4"			
1 1/2"			
2"			
2 1/2"			
3"			
3 1/2"			
4"			
5"			
6"			
8"			
10"			
12"			
14"			
16"			
18"			