

TRETRICE PRESSURE GAUGES



#800 SERIES

Steel Case, Black Finish Bottom Outlet, 1/4" N.P.T. Phosphor Bronze Bourdon Tube, 2% Accuracy Mid Range

Stock Sizes	2 1/2" Dial	4" Dial
0-15, 0-30, 0-60, 0-100		
0-160, 0-200, 0-300 lbs.		
0-600, 0-1000 lbs.		
#800 Compound Gauges		
30 - 15 lbs.		
#800 Vacuum Gauges		
0-30"		



Coil Syphon Required with Steam Application

#500XB SERIES

Case-4 1/2"-cast aluminum (black flange), Window-clear glass, Socket-forged brass-1/4" N.P.T.

Stock Ranges	4 1/2" Dial
0-15, 0-30, 0-60, 0-100	
0-160, 0-200, 0-300 lbs.	
0-600, 0-1000 lbs.	
500XB Compound Gauges	
30 - 15 lbs.	



PRESSURE GAUGES RECALIBRATED

Send your used gauges prepaid for recalibration.

We will not proceed with any gauge that is beyond economical repair.



LIQUID FILLED PRESSURE GAUGES

No. 800 LF Series, 2 1/2", 3 1/2"

LIQUID FILLS: This gauge is standard filled with glycerin to dampen vibration and fluid pulsation.

Available Ranges:	2 1/2" Dial	3 1/2" Dial
0-15, 0-30, 0-60, 0-100		
0-160, 0-200, 0-300 lbs.		
0-600, 0-1000 lbs.		

BOURDON TUBE: Phosphor bronze.
SOCKET: Brass-1/4" N.P.T.
CASE: Nylon- black finish.
WINDOW: Acrylic plastic.

No. 450LFB Series, 4 1/2"

LIQUID FILL: This gauge can be completely filled with glycerin or silicone to dampen vibration and fluid pulsation. It also has a temperature compensating bladder to maintain accuracy.

BOURDON TUBE: Phosphor bronze with brass socket.

CASE: Black-fiberglass reinforced polypropylene.

WINDOW: Acrylic plastic - has outstanding weatherability.



Available Ranges	4 1/2" Dial
0-15, 0-30, 0-60, 0-100	
0-160, 0-200, 0-300 lbs.	
0-600, 0-1000 lbs.	

PRESSURE SNUBBERS



VNS# TG190
#872 BRASS
1/4" N.P.T.

Porous Core Liquid or Air Only

SLING PSYCHROMETER



VNS# AB002
With Black Leatherette case 8 1/2"
Humidity chart
Range 0 to 110°F



COIL SYPHONS

VNS#-ST801 #886 Angle
VNS#-ST800 #885 Straight

1/4" N.P.T. Sched. 80
Seamless Steel for Steam
1/4" IPS Price

THERMOMETERS AND ACCESSORIES

FIXED FORM INDUSTRIAL THERMOMETERS

Econo-Therm Series, Red Reading Mercury, 6 3/4" Aluminum Case, 2" plated brass socket, 3/4"

VNS#	Temp Range	
TT030	-40-10°F	#4350
TT031	30-240°F	#4350
TT032	30-300°F	#4350
TT040	-40-100°F	#4352
TT041	30-240°F	#4352
TT042	30-300°F	#4352




#4352

#4350

ADJUSTABLE ANGLE INDUSTRIAL THERMOMETERS

Adjustable Angle, Red Reading Mercury, 9" Chrome Case, plated brass socket, 3/4" N.P.T.

VNS#	Temp Range	
TT011	0-100°F	#BX91403.5
TT013	0-160°F	#BX91403.5
TT015	30-240°F	#BX91403.5
TT016	30-300°F	#BX91403.5
TT018	50-400°F	#BX31403.5



VNS# TT011

ADJUSTABLE ANGLE DIAL THERMOMETERS

3 1/2" Stainless Steel Case, Adjustable Angle, 5 ft. capillary tubing with Brass separable socket, 30°-240°F

VNS# TT085 #V80025 1/2" N.P.T.

VNS# TT070 #7-3D2 Brass Well

DIAL THERMOMETER

3 1/2" Stainless Steel Case, Adjustable Angle, Direct mount with Brass separable socket, 30°-240°F

VNS# TT005 - #V80030

VNS# TT070 - #7-3D2 Brass Well



VNS# TT085

TEMPERATURE-PRESSURE GAUGE



#PT1088 VNS#
1/2" Bottom Connected ZZPT1088S
1/2" Back Connected ZZPT1088
Gauge registers pressure from 0 lbs. to 50 lbs. Thermometer range is 60°F to 260°F. Tube 2" in length. Tapping 1/2". Weight 1 1/4" lb.



HYGROMETER

and Temperature Indicator

Show relative humidity and temperature in both Fahrenheit and Centigrade. VNS# AB001

Accurate ±3%
5" dial solid brass case.
Drilled for wall mounting

DIGITAL DP300

Range -58°to 302°F
VNS# CO001



BIMETAL THERMOMETERS

All Stainless Steel Case & Bulb 3" Dial, 4" Stem, Back Conn., 30°-240°F.

VNS# TT024

- #B83104X



POCKET DIAL THERMOMETER

Range 0°-220°F
Cat.# B81105X
VNS# TT061

