

EXPANSION JOINTS & FLEXIBLE PUMP CONNECTORS

EXPANSION COMPENSATORS



Size	Model	VNS#	OAL
3/4"	H-075-MMT	FL001	11 ¹⁵ / ₁₆ "
1"	H-100-MMT	FL002	11 ¹⁵ / ₁₆ "
1 1/4"	H-125-MMT	FL003	14 ¹ / ₁₆ "
1 1/2"	H-150-MMT	FL004	14 ¹ / ₁₆ "
2"	H-200-MMT	FL005	14 ¹ / ₁₆ "
2 1/2"	H-250-MMT	FL006	15 ⁷ / ₁₆ "
3"	H-300-MMT	FL007	15 ⁷ / ₁₆ "
4"	H-400-MMT	FL008	—

Bellows: 2 ply stainless steel
 Stroke: 1 3/4" compression, 1/4" extension; total 2"
 Maximum operating temperature: 750°F
 Maximum working pressure: 175 PSI
 Units also available in flanged, female, female X male, and sweat ends

THREADED FLEXIBLE CONNECTORS

12", 18" & 24" length in stock for immediate delivery.
 Stainless steel hose and braid, carbon steel male pipe thread ends; pressure rated to 150#.



Size	VNS#	12" Length	VNS#	18" Length	VNS#	24" Length
1/2"	AF007		AF011		AF013	
3/4"	AF057		AF061		AF063	
1"	AF107		AF111		AF113	
1 1/4"	AF157		AF161		AF163	
1 1/2"	AF207		AF211		AF213	
2"	AF257		AF261		AF263	
2 1/2"	AF307		AF311		AF312	
3"	AF357		AF361		AF363	

CUSTOM SIZES AVAILABLE

Units also available in flanged, female, female X male, sweat ends; in brass, stainless steel, carbon steel; built to order.

Aall Flex
Hyspan
Mercer
 (many others available)

Flexonics
Metraflex
Zurn

Units are available in virtually any configuration to meet your requirements.



To order your expansion joint, specify: pipe size; type of end connections; overall lengths; pressure; temperature; medium; and any special requirements. TEFLON lining available for food

i n d u s t r y .