

Vogt FORGED STEEL GATE, GLOBE AND CHECK VALVES



Vogt Forged Steel GP GATE VALVE

150-800 Pounds Service
2000 Pounds C.W.P.

- Round Bolted Bonnet
 - Bolted Gland Outside Screw and Yoke
 - Gasket Joint Solid Wedge
 - *Hard Faced Seats
- Threaded and Socket Weld Ends

Series 12111 SW-12111
PRESSURE—TEMPERATURE RATINGS

Forged Carbon Steel
800 Pounds at 850°F
600 Pounds at 900°F
2000 Pounds at 100°F



Vogt Forged METER VALVE

Series 58431T

- Union Bonnet
 - Gasket Joint
 - Screw Gland Integral Seat
 - Inside Screw One-piece Stem
- Carbon Steel

PRESSURE—TEMPERATURE RATINGS

1180 P.S.I., temperature not to exceed 750°F
4000 P.S.I., temperature not to exceed 100°F



Vogt Forged Steel GLOBE VALVE

150-800 Pounds Service
2000 Pounds C.W.P.

- Round Bolted Bonnet
 - Outside Screw and Yoke Gasket Joint
 - Loose Disc
 - *Hard Faced Integral Seat
- Threaded and Socket Weld Ends

Series 12141 SW-12141
PRESSURE—TEMPERATURE RATINGS

Forged Carbon Steel
800 Pounds at 850°F
600 Pounds at 900°F
2000 Pounds at 100°F



Series 701 PISTON CHECK

Series B701 BALL CHECK

Vogt Forged Steel GP CHECK VALVES

Horizontal Type Threaded Ends
150-800 Pounds Service
2000 Pounds C.W.P.

- Round Bolted Bonnet
 - Gasket Joint
 - *Hard Faced Integral Seats
- PRESSURE—TEMPERATURE RATINGS

800 Pounds at 850°F
600 Pounds at 900°F
2000 Pounds at 100°F



#54853

Combination Horizontal and Vertical Ball Check

Vogt Forged CARBON STEEL

- Union Bonnet
- Gasket Joint
- Integral Seat
- FULL PORT

Carbon Steel Pressure
600 P.S.I. at 900°F
TEMPERATURE RATINGS
2000 P.S.I. at 100°F

Series	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
12111								
12141								
58431T								
701								
B701								
54853								

Butterfly Valves

Pricing P.O.A.

The SSI series 125WB/LB butterfly valve is available in sizes 2" thru 48", wafer or lug body design. These valves were designed to meet the stringent requirements for HVAC, Oil & Gas and Industrial applications, or wherever positive shut-off is required for liquids, gases and slurries.

Incorporating a 200 psig pressure rating for sizes 2" thru 12" and 150 psig pressure rating for sizes 14" thru 48" the SSI series 125WB/LB valves are constructed with a cast iron body and stainless steel shafts. The discs and seats are available in a wide range of materials to meet your specific application needs.

The SSI series 125WB/LB butterfly valves are designed and manufactured for use with ANSI 125 or 150 class flanges and comply with API 609 and MSS-SP-67.

SSI can provide the series 125WB/LB butterfly valves mounted with pneumatic actuators, electric actuators, solenoids, limit switches positioners, shaft extensions, 2-way and 3-way tee linkages, and chain wheels.

